

AMENDMENTS TO THE CLAIMS

The following listing of the claims replaces all prior versions and listings of the claims in relation to the present patent application.

Listing of Claims

1. (original) A reel comprising:
a hub;
a guide member is positionable with respect to the hub such that the hub and the guide member cooperate to form a surface for receiving the magnetic tape; and
a securing mechanism for releasably securing the position of the guide member with respect to the hub.
2. (original) The reel as recited in claim 1, comprising at least one flange portion coupled to the hub, wherein the securing mechanism is coupled to the at least one flange portion.
3. (original) The reel as recited in claim 2, wherein the securing mechanism includes a resilient member configured to bias an engagement portion coupled to the resilient member into a corresponding receiving portion located on the guide member.
4. (original) The reel as recited in claim 1, wherein the securing mechanism locks the guide member and the hub to a first position and unlocks the guide member and the hub to a second position.
5. (original) The reel as recited in claim 4, wherein the securing mechanism comprises engageable tab and notch structures correspondingly located on the hub and the guide member.

6. (original) The reel as recited in claim 1, the securing mechanism comprises a biasing member to secure the position of the guide member with respect to the hub.

7. (original) The reel as recited in claim 6, wherein the securing mechanism engages the guide member to a hub in a first position and disengages the guide member to the hub in a second position.

8. (original) The reel as recited in claim 1, wherein at least one of the hub, guide member, and the securing mechanism comprises magnetic components.

9. (original) A reel comprising:

a hub;

a guide member positionable with respect to the hub such that the hub and the guide member cooperate to form a surface for winding the magnetic tape; and

a securing mechanism configured to secure the guide member to the hub, such that magnetic tape is windable onto the hub and the guide member in a first direction of rotation and a second direction of rotation while the guide member is secured to the hub.

10. (original) The reel as recited in claim 9, wherein the securing mechanism releasably engages the guide member to the hub.

11. (original) The reel as recited in claim 9, wherein the securing mechanism comprises at least one resilient member moveable to lock the position of the guide member with respect to the hub.

12. (original) The reel as recited in claim 11, wherein the securing mechanism comprises a flange with a tab.

13. (original) The reel as recited in claim 9, comprising a track portion located on the flange portion and configured to direct the guide member into engagement with the securing mechanism to form the surface in cooperation with the hub.

14. (original) The reel as recited in claim 9, wherein the first direction of rotation is a clock-wise direction and the second direction of rotation is a counter-clockwise direction.

15. (original) A magnetic tape drive system comprising:
a first reel having magnetic tape wound around the first reel;
a data head for accessing magnetic tape for storage of data;
a second reel, wherein the second reel comprises:
 a hub;
 a guide member removable from the hub and connected to the magnetic tape,
 wherein the guide member is positionable with respect to the hub such that
 the hub and the guide member cooperate to form a surface for receiving
 the magnetic tape; and
 a securing mechanism for releasably securing the position of the guide member
 with respect to the hub as the magnetic tape is wound to the second reel
 from the first reel; and
an actuation mechanism configured to rotate the first reel in a first direction to wind the
magnetic tape onto the second reel.

17.-21. (cancelled)

22. (original) A system comprising:
means for coupling a guide member to magnetic tape located on a first reel;

means for securing the position of the guide member with respect to a hub located on a second reel such that the hub and guide member cooperate to form a surface for receiving the magnetic tape, wherein the means for securing facilitates winding of tape from the first reel to the second reel in a first direction and a second direction; and

means for rotating the second reel in at least one of the first direction and the second direction.

23. -27. (cancelled)